

USB RECHARGEABLE

TACTICAL FLASHLIGHT

USB-558XL

NIGHTSTICK[®]
Life Depends on Light™



**PERFECT
EVERYDAY USE**



5.9"

5 oz



**PERFECT
EVERYDAY USE**



Waterproof sliding collar covers USB-C charging port when not in use



Red **charging indicator light** turns green when fully charged



Use the included li-ion battery for day-to-day use or **included back-up CR123 carrier** when away from a rechargeable battery source (CR123 batteries not included)



Press and holding down switch **cycles between high, medium and low modes.**

1100 LUMENS

CERTIFIED



1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2022 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

TACTICAL FLASHLIGHT

LI-ION BATTERY (INCLUDED)

ITEM NUMBER/UPC

- USB-558XL, UPC 017398806022

MARKET APPLICATIONS

- Law enforcement, security, sporting goods, fire, rescue and industrial

CERTIFICATIONS

- CE, NFPA-1971-8.6 (2013)

CASE MATERIAL

- Aircraft grade 6061-T6 aluminum with type II anodized finish

LUMENS/RUNTIME

- HIGH: 1100L, 2 hrs. runtime
 - MEDIUM: 450L, 4.5 hrs. runtime
 - LOW: 125L, 22 hrs. runtime

CANDELA

- HIGH: 13,843
 - MEDIUM: 5,447
 - LOW: 1,550

BEAM DISTANCE

- HIGH: 235 m
 - MEDIUM: 148 m
 - LOW: 79 m

WATER RATING

- IP-X7 Waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 5.9 in (150 mm)
 - BARREL DIAMETER: 1 in (25 mm)
 - BEZEL DIAMETER: 1.2 in (30 mm)
 - WEIGHT: 5.7 oz (162 g) (with batteries)

BATTERY

- Li-ion rechargeable battery, or 2 CR123 (not included) using CR123 battery carrier (included)






WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Flashlight
 - Li-ion rechargeable battery
 - CR123 battery carrier
 - USB-C charging cord (2')

- Instruction manual

FL 1 STANDARD	HIGH	MEDIUM	LOW
	1100 LUMENS	450 LUMENS	125 LUMENS
	2h	4h 30min	22h
	235m	148m	79m
	13843cd	5447cd	1550cd
	2m 1m		

CERTIFIED



NFPA

Patent #9,713,217 and #10,088,138

