

# X-Series Intrinsically Safe Dual-Light™ Flashlight

Flashlight



Floodlight



Dual-Light



TECHNOLOGY



**210** Flashlight  
Lumens

**130** Floodlight  
Lumens

**285** Dual-Light™  
Lumens

This Dual-Light™ Flashlight is cETLus, ATEX, INMETRO and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present. The XPP-5422GX uses a CREE® LED rated at 210 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 187 meters. A 130 lumens unfocused floodlight is integrated into the housing which is perfect for close-up illumination. Additionally both the flashlight and the floodlight can be turned on at the same time for maximum versatility. Power comes from 3 AA premium batteries (not included).

**INTRINSICALLY SAFE**



- cETLus, ATEX, INMETRO and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present
- Beam distance rated at 187 meters
- Engineered polymer housing

**XPP 5422GX**

# X-Series Intrinsically Safe Dual-Light™ Flashlight

## FEATURES

- cETLus, ATEX, INMETRO and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present
- Flashlight – floodlight – Dual-Light™
- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Dual-Light (flashlight & floodlight at same time) for maximum versatility
- Engineered polymer housing
- Non-slip grip
- Dual body switches
- Dustproof / Waterproof
- Impact & chemical resistant
- Built-in pocket/belt clip
- Includes removable lanyard
- Requires 3 AA batteries (not included)
- Limited Lifetime Warranty



Built in pocket/belt clip



Dual body switches



Wide-beam floodlight

## SPECIFICATIONS

- Lumens: flashlight-210, floodlight-130, dual-light-285
- Run-time: flashlight-14 hrs, floodlight-20 hrs, dual-light-10 hrs
- Beam distance: 170 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Length: 7in, head diameter: 1.8in, handle diameter: 1.5 x 1.1in, weight: 6.9oz

FL 1 STANDARD		

## INCLUDED

- Flashlight with built-in pocket/belt clip
- Removable lanyard

## SAFETY RATING

cETLus, ATEX, INMETRO and IECEx listed Intrinsically Safe

Patent 7,738,229

Model	UPC 0 17398
XPP-5422GX	80584 1