XPP-5414





Integrated floodlight for close-up illumination.



Easily activate flashlight & floodlight with **top-mounted dual** switches.



Dual light mode provides **maximum safety** and utility.




Integrated magnet on base and deep concealment reversible pocket clip for **convenient hands-free use**.



AVAILABLE AS A KIT





120 LUMENS

X-SERIES™

DUAL-LIGHT™ FLASHLIGHT

2AA

ITEM NUMBER/UPC

XPP-5414GX (light only) 0 17398 80664 0 XPP-5414GX-KO1 (light with mount) 0 17398 80665 7 NS-HMC7 (mount only) 0 17398 80666 4

MARKET APPLICATIONS

- Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- CE, cETLus, ATEX, IECEX, NFPA 1971-8.6 (2013)

CASE MATERIAL

- Glass filled nylon polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 120L, 24 hrs. runtime

FLOODLIGHT

- HIGH: 120L, 24 hrs. runtime

DUAL-LIGHT

- 120L, 24 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 3,100

BEAM DISTANCE

FLASHLIGHT

- HIGH: 111m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 m

DIMENSIONS

- LENGTH: 6.25 in (159 mm)
- BARREL DIAMETER 0.86 in (22 mm)
- BEZEL DIAMETER: 2.1 in (53mm)
- WEIGHT: 4.1 oz (116 g) (with batteries)

BATTERY

2 AA batteries (not included)

WARRANTY

- Limited lifetime warranty


WHAT'S INCLUDED

XPP-5414GX

- Removable/Reversible Pocket Clip
- Instruction manual

XPP-5414GX-K01

- NS-HMC7 multi-angle mount
- Removable/Reversible Pocket Clip
- Instruction manual





C€ 0359

Ex is FLASHLIGHT FOR USE IN HAZAPROUS L COATIONS

CLASS I DIV 1 GRPS A-D 73 Ex is op is IIC T3 Gs

Ex is op is IIC T3 Gs

Ex is IIC T3 Gs



AVAILABLE AS A KIT

