

X-Series Intrinsically Safe Low-Profile Dual-Light™ Headlamp



200 Lumens
Dual-Light™
180/100 Lumens
Spotlight
180/100 Lumens
Floodlight

This X-Series Intrinsically Safe Low-Profile Dual-Light™ Headlamp is cULus, ATEX and IECEx listed Intrinsically Safe and is designed specifically to work on fire helmets and hard-hats that have a flip-up face shield. The unique low-profile shape allows the user to work without having to remove the headlamp when raising or lowering their face shield. The XPP-5460GX is manufactured from glass-filled nylon polymer and features a multi-position tilt head design. Both the spotlight and the floodlight use LEDs and an advanced (TIR) Total Internal Reflection lens designed to optimize lumen output and beam pattern. Front mounted dual switches provide easy access to the spotlight for distance illumination, the floodlight for close-up illumination, and Dual-Light for maximum lighting, versatility and user safety. The XPP-5460GX includes a heavy-duty rubber head strap for use on a fire helmet or hard-hat, and is powered by 3 AAA batteries (included).

INTRINSICALLY SAFE



- Low-profile design
- cULus, ATEX, and IECEx listed Intrinsically Safe
- Beam distance rated at 106 meters
- Polymer housing

XPP 5460GX

X-Series Intrinsically Safe Low-Profile Dual-Light™ Headlamp

FEATURES

- cULus, ATEX and IECEx listed Intrinsically Safe
- LED technology
- Focused high/low-brightness spotlight beam for distance illumination
- Unfocused high/low-brightness wide-beam floodlight for close-up illumination
- Dual-Light™ (spotlight and floodlight on at the same time) for maximum versatility
- Glass-filled nylon polymer housing
- (TIR) Total Internal Reflection lens designed to optimize lumen output and beam pattern
- Dual switches located on front of light
- Adjustable tilt head
- Heavy-duty rubber strap for fire helmets and hard hat applications
- Dustproof / Waterproof
- Impact & chemical resistant
- Powered by 3 AAA batteries (included)
- Limited Lifetime Warranty

INCLUDED

- Headlamp
- 3 AAA batteries
- Heavy-duty rubber hard hat strap

Model	UPC 0 17398
XPP-5460GX	80604 6

SPECIFICATIONS

- Lumens: high spotlight-180, low spotlight-100, high floodlight-180, low floodlight-100, dual-light-200
- Run-time: high spotlight-3.5 hrs, low spotlight-10 hrs, high floodlight-3.5 hrs, low floodlight-10 hrs, dual-light-3 hrs
- Beam distance: 106 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Length: 3.54in, width: 1.58in, depth: 1.875in, weight: 5.8oz

FL 1 STANDARD	DUAL-LIGHT	HIGH	LOW
	200 LUMENS	180 LUMENS	100 LUMENS
	3h	3h 30 min	10h
	78m	106m	74m
	1528cd	2799cd	1399cd
	2m		1m

SAFETY RATING

cULus, ATEX, and IECEx listed Intrinsically Safe
Meets the requirements of NFPA-1971-8.6 (2013)

Bayco Products, Inc. XPP-5460 Wylie, TX 75098	
 LISTED E 467756 INTRINSICALLY SAFE SECURITE INTRINSEQUE CE 0359	Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS CLASS I DIV 1 GRPS A-D T4 Ex ia IIC T4 Ga CLASS II & III DIV 1 GRPS E-G DEMKO 17 ATEX 1824 CLASS I ZONE 0 GRP IIC T4 IECEx UL 17.0003 CLASS II ZONE 20 IIC T135°C -20°C ≤ Tamb ≤ +40°C Ⓜ II 1 G Ex ia IIC T4 Ga 1.5V/Cell / E92 or EN92
WARNINGS: Replace batteries in a non-hazardous location. Use only Energizer Model E92 or EN92 batteries.	
AVERTISSEMENT: Remplacer les piles dans une zone non dangereuse. Utiliser uniquement les piles Energizer AAA - modèle E92 ou EN92.	