

**ZONE 1/21** 

CLI/DIV 1



4

**IS930.1** 

The IS930.1 is the tablet for use in ATEX Zones 1/21 and 1/CI I Div1. The 8" tablet is highly robust, powerful and offers many technical advantages: 8.400 mAh Battery, Qualcomm Snapdragon SDM 660, NFC, Android™ 9.

) Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. ) i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Android is a trademark of Google LLC. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth's is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi'e is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. ) © 2020 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1030MD01REV03\_EN 0.8.2020





## **TECHNICAL FEATURES**



ATEX approved: EX-Zone 1/21 II 2G Ex ib IIC T4 Gb II 2D Ex ib IIIC T135°C II 2D Ex ib IIIC T135°C



IECEx approved: Ex-Zone 1/21 Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X



NEC500 approved: Class I, II, III Division 1 Groups A B C D E F G, T4 Intrinsically Safe



EAC approved: 1Ex ib IIC T4 Gb X Ex ib IIIC T135°C Db X



Android 9



GSM 850/900/1800/ 1900 MHz WCDMA: UMTS B1/2/4/5/8 LTE-TDD: B38/B39/B40/B41 LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/ 26/28A/28B/29/30/66 TD-SCDMA: B34/B39



2,4GHz + 5GHz: IEEE 802.11a/ b/g/n/ac/e/k/r/h with max. 8 connections hotspot



Bluetooth® 5

external memory



Qualcomm Snapdragon SDM660 Octa-Core Kryo Gold-Quad cores 2.2GHz Kryo Silver-Quad cores 1.8GHz 64 GB internal memory 54 GB accessible



size: 237 x 156 x 22 mm, weight: 890 g



magnetic charging port

microSD up to 128 GB



2 cameras: 13 MP AF rear camera and 5 MP front camera



SOS-key Loneworker protection LWP ready (third party application required, based on country specific regulations)



Near Field

Communication



waterproof: 1 hour up to 2 m, impervious to dust and microparticles



operation range from -20 °C to 60 °C



8" multi capacitive touchscreen with a resolution of 1200 x 1920 pixel, RugDisplay-Glass



usable with gloves



8.400 mAh battery



GPS, A-GPS, Glonass, Beidou, Galileo



Proximity, acceleration, light, barometer and magnetic sensor



Tablet with integrated battery, charger, i.safe PROTECTOR 2.0 USB cable, i.safe PROTECTOR 3.0 USB cable, quick start manual and safety instructions