

SIM card -  
easy to install



## GROUP I M1 MINING



android  
enterprise  
recommended



- › Very high level of safety in the mining sector with the risk of firedamp
- › Zero-touch capable
- › Android™ 10  
Upgrade to Android™ 13 (available Q3/2023)

‹ IS930.M1 ›

The robust, powerful and particularly dust-proof tablet of the Industry 4.0 generation is ideal for use in the mining industry. The Android Enterprise Recommended device can be used immediately thanks to its zero-touch functionality and is ideally suited for maintenance applications in the IoT environment. The 8-inch display, two freely programmable buttons, a long-life battery, a practical hand strap, leather bag with a shoulder/belt or carry strap system are further highlights.

› All trademarks and copyrights are the properties of their respective owners. › © 2023 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1030MD03REV07\_EN\_04.2023



< IS930.M1 >



ATEX approval: Mining  
Ex ia I Ma IP64



IECEx approval: Mining  
Ex ia I Ma IP64



ANZEx approval: Mining  
Ex ia I Ma  
-20 °C ≤ Ta ≤ +60 °C



EAC approval: Mining  
PB Ex ib I Mb X

Further approvals: SANS (South Africa)

## TECHNICAL FEATURES

<b>Operating system</b>	Android™ 10   Upgrade to Android™ 13 (available Q3/2023)
<b>Processor</b>	SDM660 Octa-Core (Kryo Gold-Quad cores 2,2 GHz; Kryo Silver-Quad cores 1,8 GHz)
<b>Memory</b>	4 GB RAM   64 GB internal memory   microSD memory up to 512 GB
<b>Frequencies</b>	2G GSM: 850/900/1800/1900 MHz 3G WCDMA: UMTS B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/26/28A/28B/29/30/66 4G LTE-TDD: B38/B39/B40/B41 4G LTE-SCDMA: B34/B39
<b>Dimensions</b>	size: 237 x 156 x 22 mm   weight: 890 g
<b>Display</b>	8" Gorilla Glass® 3. generation   1200 x 1920 pixels
<b>Battery</b>	8400 mAh
<b>Camera</b>	13 MP AF rear camera   5 MP FF front camera
<b>Connections</b>	WiFi 2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with max. 8 connections hotspot Bluetooth® 5 GPS, A-GPS, Glonass, Beidou, Galileo Near Field Communication
<b>Types of protection</b>	IP68 dust-/waterproof   MIL-STD-810H   usable from -20 °C to +60 °C

## FURTHER FEATURES



SOS key for loneworker protection  
LWP ready (third party application required,  
based on country specific regulations)



2 freely programmable keys



Usable with gloves



Accelerometer, gyroscope, magnetic,  
temperature and humidity, proximity sensors



Magnetic charger port

## SET CONTENT

Tablet with integrated battery, Hand Strap, i.safe PROTECTOR 2.0 Type C USB Cable, i.safe PROTECTOR 3.0 USB Magnetic Charger Cable, Power Adapter universal, Display Protection Foil, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.